

## DECLARATION OF PERFORMANCE

**N° 0101/051**

**Rev. 0**

Product Identification Code	Flat product made of Stainless Steel X5CrNi18-10 1.4301 Cold rolled, according to EN10088-4.
Identification	According to the information stated on the ID label with barcode and/or bundle number and in the inspection certificate.
Intended use of the construction product	Stainless Steel Flat Product for use in the construction field.
Manufacturer (registered office)	<b>Marcegaglia S.p.A.</b> Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
Production Plant	<b>Gazoldo Degli Ippoliti</b> Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
System of assessment and verification of the continuity of performance of the construction product	<b>2+</b>
Name and ID number of the notified Body	RINA Services S.p.A. – Via Corsica, 12 – 16128 Genova - Italia <b>0474</b>

Certificates of Conformity for the control of the plant production have been issued for the following elements:

- Starting inspection of the production plant and of the factory production control.
- Surveillance, evaluation and regular audits of the factory production control

### DECLARED PERFORMANCE

Main Features	Performance	Harmonised specification
Dimensional Tolerances	As per Table 2	EN9445-2:2009
Elongation	As per Table 1	EN10088-4
Tensile strength		
Yield strength 0,2%		
Impact strength		
Weldability (Chemical Analysis)	According to specification	
Durability (Chemical Analysis)	As per Table 1	
Resistance to brittle fracture (see Impact Strength)		
Cold Forming (see Elongation)		

This declaration of performance is issued under the sole responsibility of the manufacturer identified above

Signed for and on behalf of Marcegaglia S.p.A.

**Arnaldo Ing. Barini**  
Gazoldo d.l. Plant Manager.

*Gazoldo D.l. 01/07/2013*

This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate issued after delivery

**Table 1 – Mechanical properties of Cold Rolled Austenitic Steel**

Product Grade			Type of product	Thk mm	Yield Strength		Tensile Strength R <sub>m</sub> MPa <sup>(g)</sup>	Elongation Fracture		Impact strength ISO-V KV		Intergranular corrosion resistance <sup>(f)</sup> Conditions of the supply
Quality	No.	Aisi			R <sub>p0,2</sub>	R <sub>p1,0</sub> <sup>(b)</sup>		A <sub>80</sub> <sup>(d)</sup> < 3mm T %	A <sup>(e)</sup> ≥ 3mm T %	> 10mm T.		
							MPa <sup>(g)</sup> min Transversal <sup>(c)</sup>			J min Long.	J min Transv.	
<b>X5CrNi18-10</b>	<b>1.4301</b>	<b>304</b>	(a) C	8	230	260	540±750	45	45	-	-	Yes

a) Type of Product: C = Cold Rolled, H = Hot Rolled  
 b) Value given as an indication only  
 c) For Continuous Hot Rolled products the min. value of R<sub>p0,2</sub> must be increased by 20MPa and the minimum value of R<sub>p1,0</sub> must be increased by 10MPa.  
 d) Values may apply to samples 80 mm long and 20 mm. wide, as well as 50 mm long and 12,5 mm wide  
 e) Values apply to samples having 5,65√S<sub>0</sub>.  
 f) When required, it must comply with EN ISO 3651-2  
 g) 1 MPa = 1N/mm<sup>2</sup>

**Table 2 – Dimensional Tolerances EN9445-2**

Tolerances of thickness for Wide Strips as per method A										
Thickness range		Regular Tolerance For widths ≤ 2100mm			Special Tolerances (S) for Nominal Widths W					
					W ≤ 1000	1000 < W ≤ 1300	1300 < W ≤ 2100			
≥ 0,60 < 0,80		± 0,050			± 0,035	± 0,040		-		
≥ 0,80 < 1,00		± 0,060			± 0,040	± 0,045		± 0,050		
≥ 1,00 < 1,20		± 0,070			± 0,045	± 0,045		± 0,050		
≥ 1,20 < 1,50		± 0,080			± 0,050	± 0,055		± 0,060		
≥ 1,50 < 2,00		± 0,090			± 0,055	± 0,060		± 0,070		
≥ 2,00 < 2,50		± 0,100			-	-		-		
≥ 2,50 < 3,00		± 0,120			-	-		-		
≥ 3,00 < 4,00		± 0,140			-	-		-		

Above tolerances apply to the measurement method A as per point 17.2 of EN Rule, which allows to measure anywhere within 20 mm. from the edge in case of trimmed edges, or within 30 mm from edge if left untrimmed from rolling

Nominal Width		Tolerance (mm)
≤ w < 1000		-0 +25
1000 ≤ w ≤ 2100		-0 +30

Tolerances of thickness for strips and sheets from Wide Strips										
Nominal thickness t		Regular Tolerances for Width w			Special Tolerances for Width w					
		w ≤ 1000	1000 < w ≤ 1300	13 000 < w ≤ 2100	w ≤ 1000	1000 < w ≤ 1300	13 000 < w ≤ 2100			
0.8	≤ t < 1.00	±0.055	±0.060	±0.070	±0.040	±0.050	±0.050			
1.00	≤ t < 1.20	±0.070	±0.070	±0.080	±0.050	±0.055	±0.060			
1.20	≤ t < 1.50	±0.080	±0.080	±0.100	±0.055	±0.060	±0.060			
1.50	≤ t < 2.00	±0.080	±0.090	±0.110	±0.065	±0.070	±0.080			
2.00	≤ t < 2.50	±0.090	±0.110	±0.130	-	-	-			
2.50	≤ t < 3.00	±0.110	±0.130	±0.150	-	-	-			
3.00	≤ t < 4.00	0.140	±0.150	±0.160	-	-	-			

Tolerances of width for strips and sheets from Wide Strips										
Nominal thickness t		Regular Tolerances for Width w				Special Tolerances for Width w				
		w ≤ 125	125 < w ≤ 250	250 < w ≤ 600	600 < w ≤ 1000	1000 < w ≤ 2100	w ≤ 125	125 < w ≤ 250	250 < w ≤ 600	
	t < 1.00	-0 +0.5	-0 +0.50	-0 +0.7	-0 +1.5	-0 +2.0	-0 +0.3	-0 +0.3	-0 +0.6	
1.00	≤ t < 1.50	-0 +0.7	-0 +0.70	-0 +1.0	-0 +1.5	-0 +2.0	-0 +0.4	-0 +0.5	-0 +0.7	
1.50	≤ t < 2.50	-0 +1.0	-0 +1.00	-0 +1.2	-0 +2.0	-0 +2.5	-0 +0.6	-0 +0.7	-0 +0.9	
2.50	≤ t < 3.50	-0 +1.2	-0 +1.2	-0 +1.5	-0 +3.0	-0 +3.0	-0 +0.8	-0 +0.9	-0 +1.0	

**Table 2 – Dimensional Tolerances EN9445-2**

Tolerances of Length for sheets from Wide Strips					
Nominal Length L		Regular Tolerance (mm)		Special Tolerance (mm)	
L ≤ 2000		-0 +5		-0 +3	
2000 < L		-0 +0.0025 L		-0 +0.0015 L	
Tolerances of Edge Camber for products deriving from Wide Strips					
Nominal Width w		Tolerances for size range (mm)			
		1000		2000	
10	≤ w < 40	2.5		10	
40	≤ w < 125	2		8	
125	≤ w < 600	1.5		6	
600	≤ w < 2100	1		4	
Tolerances of Squareness of sheets from Wide Strip					
Length L		Maximum difference on diagonal lengths (mm)			
	L ≤ 3000	6			
3000	< L ≤ 6000	10			
	L > 6000	15			
Tolerances of Flatness for Flat Products					
Wave Height h / Wave Length L ≤ 0,03 (for all thicknesses)					
Tolerances of Edge Displacement for Coils (each side)					
Trimmed Edges		35mm			
Untrimmed Edges		70mm			