

DECLARATION OF PERFORMANCE

No. 0104/007

Rev. 1

Product identification code	Hot rolled steel product for Structural Use Grade S355JR as per EN10025-2:2004
Identification	According to the information stated on the ID label with barcode and/or Bundle number and in the Inspection Certificate
Intended use of the Construction Product	Flat product for use in metal structures or in metal complexes and concrete structures
Manufacturer (registered office)	Marcegaglia S.p.A. Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
Production Plant	Ravenna Via Baiona n°141- 48123 Ravenna Italia
System of assessment and verification of constancy of performance of the construction product	2+
Notified Body and ID No	RINA Service S.p.A. – Via Corsica, 12 – 16128 Genova - Italia 0474

Certificates of Conformity for the control of the plant production have been issued for the following elements:

- Starting inspection of the production plant and of the factory production control
- surveillance, evaluation and regular audits of the factory production control

DECLARED PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Dimensional tolerances	As per Table 2	EN10051:2010
Elongation	As per Table 1	EN10025-1:2004 EN10025-2:2004
Tensile strength		
Yield strength		
Impact strength		
Weldability (CEV)	0.45% max	
Durability (with no request for coating)	N.P.D.	

This declaration of performance is issued under the sole responsibility of the Manufacturer identified above

Signed for and on behalf of Marcegaglia S.p.A.

Aldo Dr. Fiorini
Ravenna Plant Manager

Ravenna 01/07/2013

This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate issued after delivery

TABLE 1 – MECHANICAL CHARACTERISTICS

Mechanical characteristics at room temperature for steel grades with impact strength values												
GRADE	$R_{eH}^{(a)}$ MPa ^(bb)	$R_m^{(a)}$ MPa ^(b)		Min. Percentage elongation after break % ^{a)}							Longitudinal Impact strength KV	
	Min			$L_0 = 80$ (mm)					$L_0 = 5,65\sqrt{S_0}$	Temp. (°C)	Min energy (J)	
	Nominal Thickness (mm)											
	≤ 16	< 3	≥ 3 ≤ 100	a)	≤ 1	> 1 ≤ 1.5	> 1.5 ≤ 2	> 2 ≤ 2.5	> 2.5 < 3	≥ 3 ≤ 40	> 6 ≤ 150	
S355JR	355	510 ÷ 680	470 ÷ 630	L	14	15	16	17	18	22		
				t	12	13	14	15	16	20		27

a) For sheets and strips ≥600 mm wide, the transversal (t) to rolling direction is applied. For all other products, the values for parallel (l) to rolling direction are applied
 b) MPa = 1N/mm²

TABLE 2 – DIMENSIONAL TOLERANCES

tolerance on thickness – dimension mm				
NOMINAL THICKNESS	tolerances for nominal width			
	≤ 1200	> 1200 ≤ 1500	> 1500 ≤ 1800	> 1800
≤ 2,00	± 0,20	± 0,22	± 0,24	-
> 2,00 ≤ 2,50	± 0,21	± 0,24	± 0,26	± 0,29
> 2,50 ≤ 3,00	± 0,23	± 0,25	± 0,28	± 0,30
> 3,00 ≤ 4,00	± 0,25	± 0,28	± 0,30	± 0,31
> 4,00 ≤ 5,00	± 0,28	± 0,30	± 0,32	± 0,33
> 5,00 ≤ 6,00	± 0,30	± 0,32	± 0,33	± 0,36
> 6,00 ≤ 8,00	± 0,33	± 0,35	± 0,36	± 0,40
> 8,00 ≤ 10,00	± 0,37	± 0,38	± 0,39	± 0,46
> 10,00 ≤ 12,50	± 0,40	± 0,41	± 0,43	± 0,49
> 12,50 ≤ 15,00	± 0,43	± 0,44	± 0,46	± 0,53
> 15,00 ≤ 25,00	± 0,46	± 0,48	± 0,52	± 0,58

tolerance on width - dimension mm		
NOMINAL WIDTH	raw edges	trimmed edges
≤ 1200	-0 / +20	-0 / +3
> 1200 ≤ 1850	-0 / +20	-0 / +5
> 1850	-0 / +25	-0 / +6

Tolerances on products with trimmed edges apply to nominal thickness ≤ 10mm
 For thickness > 10mm the values of + deviation must be agreed upon order placement

tolerance on length - dimension mm		
NOMINAL LENGHT	lower	upper
< 2000	-0	+10
≥ 2000 < 8000	-0	+0,005 x nominal length
≥ 8000	-0	+40

Tolerance on Flatness - dimension (mm)				
NOMINAL THICKNESS	Nominal width	Tolerances on Flatness by category		
		Category B	Category C	Category D
≤ 25	≤ 1200	18	23	To be agreed at the time of order
	> 1200 ≤ 1500	23	30	
	> 1500	28	38	

Category B = 300MPa < R_e ≤ 360MPa
 Category C = 360MPa < R_e ≤ 420MPa
 Category D = 420MPa < R_e ≤ 900MPa

tolerance on longitudinal edge camber or straightness
SHEETS with nominal length < 5000 mm $q = 0,5\%$ of length
SHEETS with nominal length ≥ 5000 mm, width ≥ 600 mm and with raw edges, $q = 20$ mm max over any portion 5000 mm long
SHEETS with nominal length ≥ 5000 mm width ≥ 600 mm and trimmed edges, $q = 15$ mm max over any portion 5000 mm long

Out of squareness
The out of squareness for sheets is the orthogonal projection of a transverse edge over a longitudinal one and must not exceed 1% of actual width of the sheet