

## DECLARATION OF PERFORMANCE

No. 0104/010

Rev. 0

Product identification code	Hot rolled steel product for Structural Use <b>Grade S355K2 as per EN10025-2</b>
Identification	According to the information stated on the ID label with barcode and/or Bundle number and in the Inspection Certificate
Intended use of the Construction Product	Flat product for use in metal structures or in metal complexes and concrete structures
Manufacturer (registered office)	<b>Marcegaglia S.p.A.</b> Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
Production Plant	<b>Ravenna</b> Via Baiona n°141- 48123 Ravenna Italia
System of assessment and verification of constancy of performance of the construction product	2+
Notified Body and ID No	RINA Service S.p.A. – Via Corsica, 12 – 16128 Genova - Italia <b>0474</b>

Certificates of Conformity for the control of the plant production have been issued for the following elements:

- Starting inspection of the production plant and of the factory production control
- surveillance, evaluation and regular audits of the factory production control

### DECLARED PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Dimensional tolerances	As per (EN10051) Table 2	EN10025-1 EN10025-2
Elongation	As per Table 1	
Tensile strength		
Yield strength		
Impact strength		
Weldability (CEV)	0.45% max	
Durability (with no request for coating)	N.P.D.	

The performance of the above mentioned product complies with the set of declared performances.

This responsibility statement is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Marcegaglia S.p.A.

*Aldo Dr. Fiorini*  
Ravenna Plant Manager

*Ravenna 15/10/2014*

This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate issued after delivery

**TABLE 1 – MECHANICAL CHARACTERISTICS**

Mechanical characteristics at room temperature for steel grades with impact strength values														
GRADE	R <sub>eH</sub> <sup>(a)</sup> MPa <sup>(b)</sup> Min	R <sub>m</sub> <sup>(a)</sup> MPa <sup>(b)</sup>		Min. Percentage elongation after break % <sup>a)</sup>							Longitudinal Impact strength KV			
				L <sub>o</sub> = 80 (mm)							L <sub>o</sub> = 5,65√S <sub>o</sub>	Temp. (°C)	Min energy (J)	
				Nominal Thickness (mm)										
				≤ 16	< 3	≥ 3 ≤ 100	a)	≤ 1	> 1 ≤ 1.5	> 1.5 ≤ 2	> 2 ≤ 2.5	> 2.5 < 3	≥ 3 ≤ 40	> 6 ≤ 150
S355K2	355	510 ÷ 680	470 ÷ 630	L	14	15	16	17	18	22	-20	27		
				t	12	13	14	15	16	20				

a) For sheets and strips ≥600 mm wide, the transversal (t) to rolling direction is applied. For all other products, the values for parallel (l) to rolling direction are applied

b) MPa = 1N/mm<sup>2</sup>

**TABLE 2 – DIMENSIONAL TOLERANCES**

tolerance on thickness – dimension mm				
NOMINAL THICKNESS	tolerances for nominal width			
	≤ 1200	> 1200 ≤ 1500	> 1500 ≤ 1800	> 1800
≤ 2,00	± 0,20	± 0,22	± 0,24	-
> 2,00 ≤ 2,50	± 0,21	± 0,24	± 0,26	± 0,29
> 2,50 ≤ 3,00	± 0,23	± 0,25	± 0,28	± 0,30
> 3,00 ≤ 4,00	± 0,25	± 0,28	± 0,30	± 0,31
> 4,00 ≤ 5,00	± 0,28	± 0,30	± 0,32	± 0,33
> 5,00 ≤ 6,00	± 0,30	± 0,32	± 0,33	± 0,36
> 6,00 ≤ 8,00	± 0,33	± 0,35	± 0,36	± 0,40
> 8,00 ≤ 10,00	± 0,37	± 0,38	± 0,39	± 0,46
> 10,00 ≤ 12,50	± 0,40	± 0,41	± 0,43	± 0,49
> 12,50 ≤ 15,00	± 0,43	± 0,44	± 0,46	± 0,53
> 15,00 ≤ 25,00	± 0,46	± 0,48	± 0,52	± 0,58

  

tolerance on width - dimension mm		
NOMINAL WIDTH	raw edges	trimmed edges
≤ 1200	-0 / +20	-0 / +3
> 1200 ≤ 1850	-0 / +20	-0 / +5
> 1850	-0 / +25	-0 / +6

Tolerances on products with trimmed edges apply to nominal thickness ≤ 10mm  
 For thickness > 10mm the values of + deviation must be agreed upon order placement

tolerance on length - dimension mm		
NOMINAL LENGHT	lower	upper
< 2000	-0	+10
≥ 2000 < 8000	-0	+0,005 x nominal length
≥ 8000	-0	+40

  

Tolerance on Flatness - dimension (mm)				
NOMINAL THICKNESS	Nominal width	Tolerances on Flatness by category		
		Category B	Category C	Category D
		≤ 25	≤ 1200	18
> 1200 ≤ 1500	23	30		
> 1500	28	38		

Category B = 300MPa < R<sub>e</sub> ≤ 360MPa  
 Category C = 360MPa < R<sub>e</sub> ≤ 420MPa  
 Category D = 420MPa < R<sub>e</sub> ≤ 900MPa

tolerance on longitudinal edge camber or straightness
SHEETS with nominal length < 5000 mm q = 0,5% of length
SHEETS with nominal length ≥ 5000 mm, width ≥ 600 mm and with raw edges, q = 20 mm max over any portion 5000 mm long
SHEETS with nominal length ≥ 5000 mm width ≥ 600 mm and trimmed edges, q = 15 mm max over any portion 5000 mm long

  

Out of squareness
The out of squareness for sheets is the orthogonal projection of a transverse edge over a longitudinal one and must not exceed 1% of actual width of the sheet