



DECLARATION OF PERFORMANCE

No 0160/012

Rev. 0

Product Identification Code	Hot rolled steel product for Structural Use. Grade S275NL as for EN10025-3:2005	
Identification	According to the information stated on the ID label with barcode and/or Bundle number and in the Inspectin certificate.	
Intended use of the Construction Product	Flat product for use in metal structures or in metal complexes and concrete structures.	
Manufacturer (registered office)	Marcegaglia S.p.A. Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia	
Production Plant	San Giorgio di Nogaro Via Fermi, n°33 - 33058 San Giorgio Nogaro (UD) - Italia	
System of assessment and verification of the continuity of performance of the construction product	2+	
Name and ID number of the notified Body	RINA Service S.p.A. – Via Corsica, 12 – 16128 Genova - Italia 0474	
Certificates of Conformity for the control of the plant production have been issued for the following elements: <ul style="list-style-type: none"> Starting inspection of the production plant and of the factory production control. Surveillance, evaluation and regular audits of the factory production control. 		
DECLARED PERFORMANCE		
Main Features	Performance	Harmonised specification
Dimensional tolerances	As for Table 2	EN 10029: 2011
Elongation	As for Table 1	EN 10025-2: 2005
Tensile strength		
Yield strength		
Impact strength		
Chemical analysis	As for Table 3	
Durability (with no request for coating)	N.P.D.	
This declaration of performance is issued under the sole responsibility of the Manufacturer identified above.		
Signed for and behalf of Marcegaglia S.p.A.		
Marco Ing. Ferrone San Giorgio di Nogaro Plant Manager		San Giorgio di Nogaro 11/07/2013
This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate.		



TABLE 1 – MECHANICAL CHARACTERISTICS

	<i>Minimum Yield strenght $R_{eH}^{a)}$ Mpa</i>					<i>Tensile strenght $R_m^{a)}$ Mpa</i>	
	Nominal Thickness (mm)						
grade	≤ 16	> 16 ≤ 40	> 40 ≤ 60				≥ 3 ≤ 100
S275NL	275	265	255				370 to 510

a) For plate, strip and wide flats with widths. ≥600 mm the direction transverse (t) to the rolling direction applies. For all other products the values apply for the direction parallel (l) to the rolling direction..

TABLE 1 – MECHANICAL CHARACTERISTICS (follows)

	<i>Mechanical characteristics at room temperature for steel grades with impact strenght values ^{a)}</i>				<i>Impact strenght KV longitudinal for flat products</i>		
	Min. percentage elongation after break % L0=5,65V50				temperature °C	Minimum energy (J)	
grade	Nominal Thickness (mm)						
	≤ 16	> 16 ≤ 40	> 40 ≤ 60			≤ 60	
S275NL	24	24	24			-50	27

a). For plate, strip and wide flats with widths. ≥600 mm the direction transverse (t) to the rolling direction applies. For all other products the values apply for the direction parallel (l) to the rolling direction.
b). This value corresponds with .27J at -30°C

TABLE 3 – CHEMICAL ANALYSIS

	<i>Chemical composition of the ladle analysis for flat products of steel grades and qualities with values for impact strenght</i>														<i>Maximum CEV based on the ladle analysis ^{c)}</i>
	C % max	Si % max	Mn %	P % max	S % max ^{a)}	Nb % max	V % max	Al tot % max ^{b)}	Ti % max	Cr % max	Ni % max	Mo % max	Cu % max	N % max	Nominal thickness (mm)
grade															≤ 60
S275NL	0,16	0,40	0,50 - 1,50	0,025	0,020	0,05	0,05	0,02	0,05	0,30	0,30	0,10	0,55	0,015	0,400

a) For railway applications a maximum S content of 0.010% may be agreed at the time of enquiry and order.
b) If sufficient other N-binding elements are present the minimum total Al content does not apply.
c) The optional increase of elements capable of influencing the CEV shall be determined by the norm.



TABLE 2 – DIMENSIONAL TOLERANCES

Tolerance on thickness (mm)

Dimensions (mm)	class A		class B		class C		class D	
	min	max	min	max	min	max	min	max
8 ≤ t < 15	-0,5	+0,9	-0,3	+1,1	0	+1,4	-0,7	+0,7
15 ≤ t < 25	-0,6	+1,0	-0,3	+1,3	0	+1,6	-0,8	+0,8
25 ≤ t < 40	-0,7	+1,3	-0,3	+1,7	0	+2	-1,0	+1,0
40 ≤ t < 80	-0,9	+1,7	-0,3	+2,3	0	+2,6	-1,3	+1,3
80 ≤ t < 150	-1,1	+2,1	-0,3	+2,9	0	+3,2	-1,6	+1,6

Tolerances on width for plates with trimmed edges ^{a)}

Dimensions (mm)	Tolerance on width for trimmed edges	
Nominal thickness t	Lower	Upper
t < 40	0	+20
40 ≤ t < 150	0	+25

a) Tolerances on width for plates with untrimmed edges shall be the subject of agreement between the manufacturer and purchaser at the time of enquiry and order

Tolerances on length

Dimensions (mm)	Tolerances on length	
Nominal length t	Lower	Upper
l < 4000	0	+20
4000 ≤ l < 6000	0	+30
6000 ≤ l < 8000	0	+40
8000 ≤ l < 10000	0	+50
10000 ≤ l < 15000	0	+75
15000 ≤ l ≤ 20000	0	+100

Tolerances on flatness

Dimensions (mm)	Normal tolerances (class N)		Special tolerances (class S)	
	Measuring length (mm)		Measuring length (mm)	
Nominal thickness t	1000	2000	1000	2000
8 ≤ t < 15	7	11	3	6
15 ≤ t < 25	7	10	3	6
25 ≤ t < 40	6	9	3	6
40 ≤ t < 150	5	8	3	6

For anything not specified in tables or for exceptions as established in the reference standards