


<b>DECLARATION OF PERFORMANCE</b>		
<b>NR C3009</b>		<b>Rev. 0</b>
Product Identification Code	Welded tube made of structural steel S275J2H in accordance with EN10219	
Identification	According to the information stated on the ID label with barcode / bundle number and bundle number in the inspection certificate.	
Destiny and scope of application of product	Cold formed welded structural hollow sections of round, square, or rectangular shape for structural uses.	
Manufacturer (registered office)	<b>Marcegaglia Poland Sp.zo.o.</b> Ul. Kaliska 72, 46-320 Praszka - Poland	
Production Plant	<b>Ligota Dolna</b> Ul. Przemysłowa 1, 46-320 Kluczbork - Poland	
System of assessment and verification of the continuity of performance of the construction product	<b>2+</b>	
Name and ID number of the notified Body	RINA Service S.p.A. – Via Corsica, 12 – 16128 Genova - Italia <b>0474</b>	
Certificates of Conformity for the control of the plant production have been issued for the following elements: <ul style="list-style-type: none"> <li>• initial inspection of the production plant and of the factory production control.</li> <li>• surveillance, evaluation and regular audits of the factory production control.</li> </ul>		
<b>DECLARED PERFORMANCE</b>		
Main Features	Performance	Harmonised specification
Dimensional Tolerances	As per Table 2	EN10219-2:2006
Elongation	As per Table 1	EN10219-1:2006
Tensile strength		
Yield strength		
Impact strength		
Weldability (CEV)		
Durability	N.P.D.	
This declaration of performance is issued under the sole responsibility of the manufacturer identified above.		
Signed for and on behalf of Marcegaglia Poland Sp.zo.o:		
 <b>Filippo Nicoli</b> <i>Plant Director</i>		<i>Ligota Dolna, 01.07.2013</i>
This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate issued at the delivery.		

**Table 1 – Mechanical properties**

Steel grade		Minimum yield strength $R_{eH}$	Tensile strength $R_m$		Minimum elongation % <sup>(b)</sup>	Minimum impact energy	
Steel name	Steel number	[MPa]	[MPa]		$L_0=5.65\sqrt{S_0}$	KV in J <sup>(c)</sup>	
		Nominal thickness in mm					Test temperature
		$\leq 16$	$< 3$	$\geq 3 \leq 40$	$\leq 40$		
S275J2H	1.0138	275	430+580	410+560	20 <sup>(a)</sup>	-20°	27
a. For proportion $D/T < 15$ (round) and $(B+H)/2T < 12,5$ (square, rectangular) minimum is decreased by 2 b. For thickness $< 3,0$ mm the percentage elongation may be reported for a length of 80 mm or 50 mm c. Impact test, when applicable or required, shall be carried out in accordance with EN10219-1. Impact test are not required for nominal thickness $< 6$ mm.							

Parameter	Round hollow sections	Square and rectangular hollow sections
<b>External dimension (D, B and H)<sup>(4)</sup></b>	$\pm 1\%$ with min value of $\pm 0,5$ mm and max value of $\pm 10$ mm	H, B $< 100$ mm $\Rightarrow \pm 1\%$ with min value of $\pm 0,5$ mm $100$ mm $\leq$ H, B $\leq 200$ mm $\Rightarrow \pm 0,8\%$ H, B $> 200$ mm $\Rightarrow \pm 0,6\%$
<b>Thickness (T)</b>	for D $\leq 406,4$ mm: T $\leq 5$ mm $\Rightarrow \pm 10\%$ T $> 5$ mm $\Rightarrow \pm 0,5$ mm for D $> 406,4$ mm $\pm 10\%$ with max value of $\pm 2$ mm	T $\leq 5$ mm $\Rightarrow \pm 10\%$ T $> 5$ mm $\Rightarrow \pm 0,5$ mm
<b>Roundness deviation (O)</b>	2% for hollow sections with proportion of diameter to thickness lower than 100 <sup>(1)</sup> , where the roundness deviation is calculated for the formula: $O(\%) = \frac{D_{max} - D_{min}}{D} * 100$	
<b>Concavity / Convexity (x<sub>1</sub>, x<sub>2</sub>)<sup>(2)</sup></b>		Max. 0,8% with minimum value of 0,5mm, using the formula: $\frac{x_1}{B} * 100\%; \frac{x_1}{H} * 100\%; \text{ etc.}$
<b>Squareness of side (<math>\theta</math>)</b>		$90^\circ \pm 1^\circ$
<b>Corner radius (C<sub>1</sub>, C<sub>2</sub> or R)</b>		T $\leq 6$ mm $\Rightarrow 1,6T + 2,4T$ 6 $< T \leq 10$ $\Rightarrow 2,0T + 3,0T$ 10 $< T \Rightarrow 2,4T + 3,6T$
<b>Twist (V)</b>		2mm + 0,5 mm/m of length
<b>Straightness (e)</b>	0,20 % of total length and 3mm for each meter	0,15 % of total length and 3mm for each meter
<b>Mass (M)</b>	$\pm 6\%$ for individual hollow section	
<b>Length deviation (T)<sup>(3)</sup></b>	Exact lengths	$< 6000$ mm $\Rightarrow 0; + 5$ mm
		$6000$ mm $\leq L \leq 10000$ mm $\Rightarrow 0; + 15$ mm
		$> 10000$ mm $\Rightarrow 0; + 5$ mm + 1mm/m
	Approximate lengths	$> 4000$ mm $\Rightarrow 0; + 50$ mm
<sup>1.</sup> When the proportion $D/T > 100$ , then the roundness deviation shall be agreed. <sup>2.</sup> The tolerance of convexity and concavity is independent of the external dimensions' tolerances. <sup>3.</sup> At the stage of inquiry or order, the manufacturer shall agree the specific type of length and length range or length. <sup>4.</sup> Dimensional measures will be made at the distance of at least 100 mm from the end of the hollow section.		