

**DECLARATION OF PERFORMANCE**
**No 0101/035**
**Rev. 3**

Product Identification Code	Hot rolled steel product for Structural Use. <b>Grade S275J2 as per EN10025-2:2019</b>
Identification	According to the information stated on the ID label with barcode and/or Bundle number and in the Inspection Certificate.
Intended use of the Construction Product	Flat product for use in metal structures or in metal complexes and concrete structures.
Manufacturer (registered office)	<b>Marcegaglia Carbon Steel</b> Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
Production Plant	<b>Gazoldo Degli Ippoliti</b> Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
System of assessment and verification of the continuity of performance of the construction product	<b>2+</b>
Name and ID number of the notified Body	RINA Services S.p.A. – Via Corsica, 12 – 16128 Genova - Italia <b>0474</b>

Certificates of Conformity for the control of the plant production have been issued for the following elements:

- Starting inspection of the production plant and of the factory production control.
- surveillance, evaluation and regular audits of the factory production control

**DECLARED PERFORMANCE**

Main Features	Performance	Harmonised specification
Dimensional tolerances	EN10051:2010	
Elongation	EN10025-2:2019	EN10025-1:2004
Tensile strength		
Yield strength		
Impact strength		
Weldability (CEV)		
Durability (with no request for coating)	N.P.D.	

The performance of the above mentioned product complies with the set of declared performances.

This responsibility statement is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Marcegaglia Carbon Steel

 Arnaldo Ing. Barini  
 Gazoldo D.I. Plant Manager



Gazoldo D.I. 02/12/2019

This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate issued after delivery.

**TABLE 1 – MECHANICAL CHARACTERISTICS**

Mechanical characteristics at room temperature for steel grades with impact strength values															
GRADE	R <sub>eH</sub> <sup>(a)</sup> MPa <sup>8b)</sup> Min	R <sub>m</sub> <sup>(a)</sup> MPa <sup>(b)</sup>			Min. Percentage elongation after break % <sup>a)</sup>							Longitudinal Impact strength KV			
					L <sub>0</sub> = 80 (mm)							L <sub>0</sub> = 5,65√S <sub>0</sub>	Temp. (°C)	Min energy (J)	
					Nominal Thickness (mm)										
					≤ 16	< 3	≥ 3 ≤ 100	a)	≤ 1	> 1 ≤ 1.5	> 1.5 ≤ 2	> 2 ≤ 2.5	> 2.5 < 3	≥ 3 ≤ 40	> 6 ≤ 150
S275J2	235	430 ÷ 580	410 ÷ 560	L	15	16	17	18	19	23	-20	27			
				t	13	14	15	16	17	21					

a) For sheets and strips ≥600 mm wide, the transversal (t) to rolling direction is applied. For all other products, the values for parallel (l) to rolling direction are applied

b) MPa = 1N/mm<sup>2</sup>

**TABLE 2 - DIMENSIONAL TOLERANCES**

Tolerance on Thickness – dimension (mm)				
NOMINAL THICKNESS	Tolerances for nominal width			
	≤ 1200	> 1200 ≤1500	> 1500 ≤1800	> 1800
≤ 2,00	± 0,17	± 0,19	± 0,21	-
> 2,00 ≤ 2,50	± 0,18	± 0,21	± 0,23	± 0,25
> 2,50 ≤ 3,00	± 0,20	± 0,22	± 0,24	± 0,26
> 3,00 ≤ 4,00	± 0,22	± 0,24	± 0,26	± 0,27
> 4,00 ≤ 5,00	± 0,24	± 0,26	± 0,28	± 0,29
> 5,00 ≤ 6,00	± 0,26	± 0,28	± 0,29	± 0,31
> 6,00 ≤ 8,00	± 0,29	± 0,30	± 0,31	± 0,35
> 8,00 ≤ 10,00	± 0,32	± 0,33	± 0,34	± 0,40
>10,00 ≤ 12,50	± 0,35	± 0,36	± 0,37	± 0,43
> 12,50 ≤15,00	± 0,37	± 0,38	± 0,40	± 0,46
>15,00 ≤ 25,00	± 0,40	± 0,42	± 0,45	± 0,50

  

Tolerance on width - dimension (mm)		
NOMINAL WIDTH	Raw edges	Trimmed edges
≤ 1200	-0 / +20	-0 / +3
> 1200 ≤ 1850	-0 / +20	-0 / +5
> 1850	-0 / +25	-0 / +6

Tolerances on products with trimmed edges apply to nominal thickness ≤ 10mm  
For thickness > 10mm the values of + deviation must be agreed upon order placement

Tolerance on Length - dimension (mm)		
NOMINAL LENGHT	Lower	Upper
< 2000	-0	+10
≥2000 < 8000	-0	+0,005 x nominal length
≥ 8000	-0	+40

  

Tolerance on Flatness - dimension (mm)			
NOMINAL THICKNESS	Nominal Width	Flatness tolerances	Special flatness tolerance
≤ 2,00	≤ 1200	18	9
	> 1200 ≤1500	20	10
	> 1500	25	13
> 2,00 ≤ 25	≤ 1200	15	8
	> 1200 ≤ 1500	18	9
	> 1500	23	12

Flatness requirements for strips must be agreed upon order placement

Tolerance on longitudinal edge camber or straightness
SHEETS with nominal length < 5000 mm q = 0,5% of length
SHEETS with nominal length ≥ 5000 mm, width ≥ 600 mm and with raw edges, q = 20 mm max over any portion 5000 mm long
SHEETS with nominal length ≥ 5000 mm width ≥ 600 mm and trimmed edges, q = 15 mm max over any portion 5000 mm long

  

Out-of-squareness
The out-of-squareness for sheets is the orthogonal projection of a transverse edge over a longitudinal one and must not exceed 1% of actual width of the sheet.