

DECLARATION OF PERFORMANCE

No 0101/038

Rev. 3

Product Identification Code	Hot rolled steel product for Structural Use. Grade S355J2 as per EN10025-2:2019
Identification	According to the information stated on the ID label with barcode and/or Bundle number and in the Inspection Certificate.
Intended use of the Construction Product	Flat product for use in metal structures or in metal complexes and concrete structures.
Manufacturer (registered office)	Marcegaglia Carbon Steel Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
Production Plant	Gazoldo Degli Ippoliti Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
System of assessment and verification of the continuity of performance of the construction product	2+
Name and ID number of the notified Body	RINA Services S.p.A. – Via Corsica, 12 – 16128 Genova - Italia 0474

Certificates of Conformity for the control of the plant production have been issued for the following elements:

- Starting inspection of the production plant and of the factory production control.
- surveillance, evaluation and regular audits of the factory production control

DECLARED PERFORMANCE

Main Features	Performance	Harmonised specification
Dimensional tolerances	EN10051:2010	
Elongation	EN10025-2:2019	EN10025-1:2004
Tensile strength		
Yield strength		
Impact strength		
Weldability (CEV)		
Durability (with no request for coating)	N.P.D.	

The performance of the above mentioned product complies with the set of declared performances.

This responsibility statement is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Marcegaglia Carbon Steel

Arnaldo Ing. Barini
Gazoldo D.I. Plant Manager



Gazoldo D.I. 02/12/2019

This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate issued after delivery.

TABLE 1 – MECHANICAL CHARACTERISTICS

Mechanical characteristics at room temperature for steel grades with impact strength values													
GRADE	$R_{eH}^{(a)}$ MPa ^{8b)} Min	$R_m^{(a)}$ MPa ^(b)			Min. Percentage elongation after break % ^{a)}						Longitudinal Impact strength KV		
					$L_0 = 80$ (mm)						$L_0 = 5,65\sqrt{S_0}$	Temp.	Min energy
	Nominal Thickness (mm)											Temp. (°C)	Min energy (J)
	≤ 16	< 3	≥ 3 ≤ 100	a)	≤ 1	> 1 ≤ 1.5	> 1.5 ≤ 2	> 2 ≤ 2.5	> 2.5 < 3	≥ 3 ≤ 40	> 6 ≤ 150		
S355J2	355	510 + 680	470 + 630	L	14	15	16	17	18	22	-20	27	
				t	12	13	14	15	16	20			

a) For sheets and strips ≥600 mm wide, the transversal (t) to rolling direction is applied. For all other products, the values for parallel (l) to rolling direction are applied
b) MPa = 1N/mm²

TABLE 2 - DIMENSIONAL TOLERANCES

Tolerance on Thickness – dimension (mm)				
NOMINAL THICKNESS	Tolerances for nominal width			
	≤ 1200	> 1200 ≤ 1500	> 1500 ≤ 1800	> 1800
≤ 2,00	± 0,20	± 0,22	± 0,24	-
> 2,00 ≤ 2,50	± 0,21	± 0,24	± 0,26	± 0,29
> 2,50 ≤ 3,00	± 0,23	± 0,25	± 0,28	± 0,30
> 3,00 ≤ 4,00	± 0,25	± 0,28	± 0,30	± 0,31
> 4,00 ≤ 5,00	± 0,28	± 0,30	± 0,32	± 0,33
> 5,00 ≤ 6,00	± 0,30	± 0,32	± 0,33	± 0,36
> 6,00 ≤ 8,00	± 0,33	± 0,35	± 0,36	± 0,40
> 8,00 ≤ 10,00	± 0,37	± 0,38	± 0,39	± 0,46
> 10,00 ≤ 12,50	± 0,40	± 0,41	± 0,43	± 0,49
> 12,50 ≤ 15,00	± 0,43	± 0,44	± 0,46	± 0,53
> 15,00 ≤ 25,00	± 0,46	± 0,48	± 0,52	± 0,58

Tolerance on width - dimension (mm)		
NOMINAL WIDTH	Raw edges	Trimmed edges
≤ 1200	-0 / +20	-0 / +3
> 1200 ≤ 1850	-0 / +20	-0 / +5
> 1850	-0 / +25	-0 / +6

Tolerances on products with trimmed edges apply to nominal thickness ≤ 10mm
For thickness > 10mm the values of + deviation must be agreed upon order placement

Tolerance on Length - dimension (mm)		
NOMINAL LENGHT	Lower	Upper
< 2000	-0	+10
≥ 2000 < 8000	-0	+0,005 x nominal length
≥ 8000	-0	+40

Tolerance on Flatness - dimension (mm)				
NOMINAL THICKNESS	Nominal width	Tolerances on Flatness by category		
		Category B	Category C	Category D
≤ 25	≤ 1200	18	23	To be agreed at the time of order
	> 1200 ≤ 1500	23	30	
	> 1500	28	38	

Category B = 300MPa < R_e ≤ 360MPa
Category C = 360MPa < R_e ≤ 420MPa
Category D = 420MPa < R_e ≤ 900MPa

Tolerance on longitudinal edge camber or straightness
SHEETS with nominal length < 5000 mm $q = 0,5\%$ of length
SHEETS with nominal length ≥ 5000 mm, width ≥ 600 mm and with raw edges, $q = 20$ mm max over any portion 5000 mm long
SHEETS with nominal length ≥ 5000 mm width ≥ 600 mm and trimmed edges, $q = 15$ mm max over any portion 5000 mm long

Out-of-squareness
The out-of-squareness for sheets is the orthogonal projection of a transverse edge over a longitudinal one and must not exceed 1% of actual width of the sheet.