

## DOP – DECLARATION OF PERFORMANCE 0160/005

DOC. 1341 Ed. 1 Rev. 00 Pag.1 di 2

DECLARATION OF PERFORMANCE							
No	0160/005						
Product Identification Code	Hot rolled steel product for Structural Use. Grade S275J0 as for EN10025-2:2019						
Identification	According to the information stated on the ID label with barcode and/or Bundle number and in the Inspectin certificate.						
Intended use of the Construction Product	Flat product for use in metal structures or in metal complexes and concrete structures.						
Manufacturer (registered office)	Marcegaglia Plates Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia						
Production Plant	San Giorgio di Nogaro Via Fermi, n°33 - 33058 San Giorgio Nogaro (UD) - Italia						
System of assessment and verification of the continuity of performance of the construction product	2+						
Name and ID number of the notified Body	RINA Service S.p.A. – Via Corsica, 12 – 16128 Genova - Italia <b>0474</b>						
Notified Body and ID No	CARES - Pembroke House, 21 Pembroke Road Sevenoaks, Kent, TN13 1XR						
	1244						

Certificates of Conformity for the control of the plant production have been issued for the following elements:

- Starting inspection of the production plant and of the factory production control.
- Surveillance, evaluation and regular audits of the factory production control.

## **DECLARED PERFORMANCE**

Main Features	Performance	Harmonised specification	
Dimensional tolerances	As for EN 10029: 2011	1	
Elongation			
Tensile strength	As for Table 1		
Yield strength	AS IOI Table I	EN 10025-2: 2019	
Impact strength		EN 10025-2. 2019	
Chemical analysis	As for Table 3		
Durability (with no request for coating)	N.P.D.		

The performance of the above mentioned product complies with the set of declared performances.

This responsibility statement is issued in accordance with Regulation (EU) No. 305/2011, under the

This responsibility statement is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

This responsibility statement is issued in accordance with Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of Marcegaglia Plates

## Marco Ing. Ferrone

San Giorgio di Nogaro Plant Manager

San Giorgio di Nogaro 12/10/2022

This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate.



## DOP – DECLARATION OF PERFORMANCE 0160/005

DOC. 1341 Ed. 1 Rev. 00 Pag. 2 di 2

TABLE 1 – MECHANICAL CHARACTERISTICS											
	Minimum Yield strenght Reh <sup>a)</sup> Mpa  Tensile strenght Rm <sup>a)</sup> Mpa										
		Nominal Thickness (mm)									
grade	≤ 16	> 16 ≤ 40	> 40 ≤ 63	> 63 ≤ 80	> 80 ≤ 100	> 100 ≤ 150	≥ 3 ≤ 100	> 100 ≤ 150			
S275J0	275	265	255	245	235	225	410 to 560	400 to 540			

a) For plate, strip and wide flats with widths. ≥600 mm the direction transverse (t) to the rolling direction applies. For all other products the values apply for the direction parallel (l) to the rolling direction..

TABLE 1 – MECHANICAL CHARACTERISTICS (follows)									
		tempe	erature fo	racteristic or steel gro trenght va	ades with	Impact strenght KV longitudinal for flat products			
		Min. po	_	longation afte =5,65√S0	r break <sup>a)</sup> %	temperature °C Minimum energy (J)			
		Nominal Thickness (mm)							
grade	Position of test pieces a)	≥ 3 ≤ 40	> 40 ≤ 63	> 63 ≤ 100 > 100 ≤ 150 ≤ 150					
	I	23	22	21	19				
S275J0						0 27			
	t	21	20	19	19				

a) For plate, strip and wide flats with widths. ≥600 mm the direction transverse (t) to the rolling direction applies. For all other products the values apply for the direction parallel (I) to the rolling direction.

	TABLE 3 – CHEMICAL ANALYSIS											
	Chemical composition of the ladle analysis for flat products of steel grades and qualities with values for impact strenght									Maximum CEV based on the ladle analysis		
	-	max for no		Si % max	Mn % max	P % max	S % max	N % max	Cu % max	Nominal thickness (mm)		
grade	≤ 16	> 16 ≤ 40	> 40							≤ 30	> 30 ≤ 40	> 40 ≤ 150
S275J0	0,18	0,18	0,18		1,50	0,030	0,030	0,012	0,55	0,40	0,40	0,42
-												

For anything not specified in tables or for exceptions as established in the reference standards