

DECLARATION OF PERFORMANCE	
NR C3007	
Rev. 6	
Unique identification code of the product type	S235JRH
Intended use/es	Metal structures or composite metal and concrete structures
Manufacturer (registered office)	Marcegaglia Poland Sp. z o.o. Ul. Kaliska 72, 46-320 Praszka - Poland
Production Plant	Ligota Dolna Ul. Przemysłowa 1, 46-200 Kluczbork - Poland
System (-s) of assessment and verification of the constancy of performance	2+
Harmonised specification	EN 10219-1:2006
Notified Body (-s)	RINA Service S.p.A. – Via Corsica, 12 – 16128 Genova - Italia 0474
Certificates of Conformity for the control of the plant production have been issued for the following elements: <ul style="list-style-type: none"> initial inspection of the production plant and of the factory production control. surveillance, evaluation and regular audits of the factory production control. 	
DECLARED PERFORMANCE	
Principal features	Performance
Dimensional Tolerances	As per EN 10219-2:2019
Elongation	As per Table 1
Tensile strength	
Yield strength	
Impact strength	
Durability	N.P.D. - possibility for hot-dip galvanizing by specifying option 1.4 at the ordering time
Weldability (CEV)	0.35% max
The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.	

Table 1 – Mechanical properties								
Steel grade		Minimum yield strength R _{eH}	Tensile strength R _m		Minimum elongation % ^(c)	Minimum impact energy		
Steel name	Steel number	[MPa]	[MPa]		Lo=5.65√So	KV in J ^(d)		
		Nominal thickness in mm					Test temperature	impact energy
		≤ 16	< 3	≥ 3 ≤ 40	≤ 40			
S235JRH ^(a)	1.0039	235	360+510	360+510	24 ^(b)	20°	27	
<div>a. Impact properties are verified only when option 1.3 is specified in the Order.</div> <div>b. See below exceptions:<div><div><input type="checkbox"/> For thickness > 3 mm and D/T section sizes < 15 (round) and (B+H)/2T < 12,5 (square and rectangular) the minimum elongation is reduced by 2.</div><div><input type="checkbox"/> For thickness ≤ 3,0 mm the minimum value for elongation is 17%</div></div></div> <div>c. For thickness < 3,0 mm the percentage elongation may be reported for a length of 80 mm or 50 mm</div> <div>d. Impact test, when applicable or required, shall be carried out in accordance with EN10219-1. Impact test are not required for nominal thickness < 6 mm.</div>								

Signed for and on behalf of Marcegaglia Poland Sp. z o.o.:

Filippo Nicoli

Marcegaglia Poland Sp. z o.o. Director

Ligota Dolna, 13.10.2025

This declaration of performance is valid only in presence of the product identification label and delivery document or of the inspection certificate issued at the delivery.